



TRIAX

connecting the future



IPTV EPG Server

Article number: 492095

Product description:

The IPTV EPG Server provides EPG data to IP-set top boxes, IP-televisions and middleware solutions, e.g. the EPG server extracts data from DVB-S and DVB-T front end modules enabling it to populate the EPG Guides on hotel IPTV displays.

Specifications

ORDER INFORMATION	
EAN Number	5702664920957
OPERATIONAL	
AC Supply voltage	100...240 / 5VDC-3000mA VAC
PSU/adapter INFO	Included Euro Plug (CEE 7/17)
PSU/adapter Art number	310019
DC Operating voltage	4.8...5.2 VDC
DC Current consumption	400 mA
Power Consumption (typ.)	2,4 W
PSU output DC voltage	5 VDC
PSU output max. DC current	3000 mA
Temperature - operating	-10...50 °C

Temperature - storage	-20 ..70 °C
Humidity - operating	20 - 80 %
Humidity - storage	10 - 90 %
CONNECTORS	
Connector I/O IP stream	RJ45 female 10/100/1000
Connector USB	USB female
Connector DC	DC jack 5.5mm/2.1mm (IEC A)
MECHANICAL	
Packing QTY	1
Product Height	44 mm
Product Width	279 mm
Product Depth	153 mm
Packaging Height	0,044 m
Packaging Width	0,280 m
Packaging Depth	0,152 m
Packaging Volume	0,002 m3
Net Weight	1,120 kg
Tara Weight	0,880 kg
Total Weight	2,000 kg
Remarks	Supported XML files: - XMLTV Format - Macnetix XML Format Max supported file size 4GB Max supported disc size 2TB Max supported filename lenght 255 char. Max. Cable length: 100 m